

ASPEN Stainless hardworking stainless steel products for hardwearing environments:  
British engineered with a lifetime guarantee.



## Product Description

The standard KB4 External Double Sided Wall Kerb is used against outside walls to provide an external drip edge and a thermal break to prevent condensation. The KB4 is designed to support the hygienic wall panel above the finish floor level to reduce the ingress of liquids and offer some protection to factory traffic. It also provides a hygienic interface between floor and wall.


Suitable for use in with tiled and screed floor.

Sizes A and C are custom to each project according to their requirements. The profile of the kerb is dependent on wall thickness.

## Technical Specification

- > 2mm 240 grit stainless steel.
- > 50mm Styrofoam to prevent frost creeping from outside of the building into the Kerb.
- > C30 concrete infill.
- > Resin anchor fixings.
- > Available in grade 316 stainless steel (British Standard 316S31, Euronorm 1.4401).
- > Compliant with EHEDG guidelines

MODEL	REF	KERB DIMENSIONS			
		A	B	C	D
DOUBLE EXTERNAL	KB4	VARIABLE	290 NOMINAL	NA	50



All dimensions in mm.



# ASPEN KB4 Wall Kerb | External Double Sided

**ASPEN**

Stainless

ASPEN Stainless hardworking stainless steel products for hardwearing environments: British engineered with a lifetime guarantee.

## ASPEN Kerbing System

As the UK based designer and manufacturer of all ASPEN Stainless, Canal Engineering is able to offer a full range of products to complete your kerbing system and can customize any of its Units or manufacture complete bespoke kerbing systems.

### Key Benefits

This profile is ideal for installing when an additional screed or tiled floor is being applied. The kerb should be installed on the base slab. The Kerb is fully welded and made to suit sliding, personnel, roller doors, corners, tees and wall ends.

### Maintenance

Stainless steel equipment should be occasionally thoroughly checked for retained deposits and concentrated fluid build up that causes corrosion.


### Cleaning

Many factors affect the choice of cleaning method and frequency of its application. Suitable methods for stainless steel are: water and steam; mechanical non abrasive scrubbing; organic solvents and mild detergents.

## ASPEN Kerbing Installation

Canal Engineering offer supply only or full installation, with fully welded and polished joints, and commissioning. Canal Engineering also offer on-going annual inspection and maintenance contracts.

For advice regarding the most suitable ASPEN Stainless for you please contact our technical sales team today to discuss your requirements.



KB4 Kerb Sample

## ASPEN Kerbing Options

> A range of tiled or screed flooring can be recommended.